DESK MASTER STATION



when**communication**is**eritical**

FEATURES

- Combined wall and desk master station with full access to all features in STENTOFON AlphaCom E exchange
- 10 programmable single touch keys with name tags
- Handset for confidential conversation
- Selectable private / open mode
- · Electret microphone with automatic sensitivity adjustment
- 1W loudspeaker



This combined desk top and wall mount master station gives full access to all features in the STENTOFON AlphaCom E exchange. The station includes both programmable single touch keys and a handset for confidential conversations. The station is also equipped with a private / open switch for choosing between direct incoming calls and announcement of calls by a ringing tone. An 1W (63 0hm) loudspeaker is provided along with a volume control bar.

Further, the station's electret microphone automatically adjusts its sensitivity according to the input level. When in conversation, the station's red lamp lights to indicate that the microphone is live. The station must be provided with a cable for connection to a wall socket. Alternative cable lengths and wall plugs are available (see next page). Required cable must be ordered separately. A bracket is included for wall mounting of the station.

Two pair twisted telephone cable (0.5 mmø / 24 AWG) is required between the exchange and the station, which can be positioned up to 1400 meters / 4600 feet away from the exchange (maximum 240 0hm loop resistance). Longer distances are possible with heavier wires.



Order Number	1007034210
Operation Voltage	Powered from exchange
Cable Requirements	2 pair twisted cable 0.5 mm2 / 24 AWG. (Max. loop resistance 240 0hm)
Temperature Range	0° C to +40° C +32° F to +104° F
Humidity Range	10% - 85% RH (non condensing)
Dimensions: (W x H x D)	225 mm x 75 mm x 176 mm 8.86" x 2.95" x 6.93"
Finish	Grey/Black ABS Plastic with structure, MT 1055



Ring Communications (UK) Ltd **Newmarket Business Centre** 341 Exning Road Newmarket Suffolk **United Kingdom**

equipment: EPKAB 98510 EPKAB 98515

ORDER NUMBER

Supplementary

1007034210

DESCRIPTION

Desk Master Station

StationCable, 3 meters / 10 feet, modular jack plug StationCable, 0.5 meter / 20 inches, modular jack plug

50 g / 2 oz 50 g / 2 oz

0.685 kg/1 lb

8 oz


SHIP WEIGHT

Tel: +44 (0)1638 660 629 e-mail: sales@ringuk.com web: www.ringuk.co.uk


DESKMASTERSTATION

Loudspeaker Output	1 W (63 Ohm)
Loudspeaker Impedance	63 Ohm
Frequency Range	300 - 5000 Hz
Microphone Output Voltage Microphonereamp.	100/300 mV 1000 Ohm
Wall SocketConnector Type	Modular jack
Indicator	LED (red)


WIRING




PINCONFIGURATION



STATIONDRAWING



WALLBRACKET DRAWING



ORDER NUMBER 1007034210

A100K10022 v.2.0

