

DESK/WALL MASTER STATION

DISPLAY



when communication is **critical**

FEATURES

- Combined wall and desk master station with full access to all features in STENTOFON AlphaCom E exchange
- Complete with a 2 x 16 character alphanumeric display providing caller identification, on-line help and a directory list
- 10 programmable single touch keys with name tags
- Selectable private / open mode
- Electret microphone with automatic sensitivity adjustment
- 1W loudspeaker and volume control bar
- Supports the volume override alarm function



DESCRIPTION

This combined desk top and wall mount master station gives full access to all features in the Stentofon exchange. The station includes programmable single touch keys and a 2 x 16 character alphanumeric display providing caller identification, on-line help and a directory service amongst other features. The station is also equipped with a private / open switch for choosing between direct incoming calls and announcement of calls by a ringing tone. An 1W (63 Ohm) loudspeaker is provided along with a volume control bar. Further, the station's electret microphone automatically adjusts its sensitivity according to the input level.

The station supports the alarm distribution function of the Stentofon exchange - ensuring broadcasting of the alarm at maximum volume. The station must be provided with a cable for connection to a wall socket. Alternative cable lengths and wall plugs are available (see next page). Required cable must be ordered separately. A bracket is included for wall mounting of the station. Two pair twisted telephone cable (0.5 mm² / 24 AWG) is required between the exchange and the station, which can be positioned up to 1400 meters / 4600 feet away from the exchange (maximum 240 Ohm loop resistance). Longer distances are possible with heavier wires.

SPECIFICATIONS

| | |
|-------------------------|--|
| Order Number | 1007071090 |
| Operation Voltage | Powered from exchange |
| Cable Requirements | 2 pair twisted cable 0.5 mm ² / 24 AWG. (Max. loop resistance 240 Ohm) |
| Temperature Range | 0° C to +40°C, +32° F to +104° F |
| Humidity Range | 10% - 85% RH (non condensing) |
| Dimensions: (W x H x D) | 168 mm x 75 mm x 176 mm 6.61" x 2.95" x 6.93" |
| Finish | Black ABS Plastic with structure MT 1055 |

Ring Communications (UK) Ltd
 Newmarket Business Centre
 341 Exning Road
 Newmarket
 Suffolk
 United Kingdom


Tel: +44 (0)1638 660 629
 e-mail: sales@ringuk.com
 web: www.ringuk.co.uk

| ORDER NUMBER | DESCRIPTION | SHIP WEIGHT |
|--------------------------|--|-----------------------|
| 1007071090 | Desk/Wall Master Station, Display | 0.540 kg/1 lb 3 oz |
| Supplementary equipment: | | |
| EPKAB 98510 | StationCable, 3 meters / 10 feet, modular jack plug | 50 g / 2 oz |
| EPKAB 98515 | StationCable, 0.5 meter / 20 inches, modular jack plug | 50 g / 2 oz |


DESKWALL MASTERSTATIONDISPLAY

| | |
|------------------------------------|----------------|
| LoudspeakeOutput | 1 W (63Ohm) |
| LoudspeakeImpedance | 63 Ohm |
| Frequency Range | 300 - 10000 Hz |
| MicrophonOutput Voltage | 100/300 mV |
| Microphone Preamp. ouput impedance | 1000 Ohm |
| Wall SockeConnector Type | Modular jack |
| Indicator | LED (red) |


WIRING




PIN CONFIGURATION



STATIONDRAWING



WALL BRACKET DRAWING



ORDER NUMBER

1007071090

DOC NO

A100K10038 v.2.0

sales@ringuk.com

